

VELP Scientifica Solutions for Overhead Stirring



	ES	LS	DLS	LH	DLH	PW
Stirring speed rpm	from 50 to 1300	from 50 to 2000	from 50 to 2000	from 50 to 2000	from 50 to 2000	from 20 to 1200
Stirring volume L	up to 15	up to 25	up to 25	up to 40	up to 40	up to 70
Operating mode	continuous	continuous	continuous / timer	continuous	continuous / timer	continuous
Digital Display			<ul style="list-style-type: none"> (set and real speed, torque and timer) 		<ul style="list-style-type: none"> (set and real speed, torque and timer) 	
Maximum viscosity mPa*s	1,000	25,000	25,000	50,000	50,000	100,000
Maximum torque Ncm	15	40	40	80	80	120
Chuck capacity mm	from 1 to 10	from 1 to 10	from 1 to 10	from 1 to 10	from 1 to 10	from 1 to 10
Counter reaction			<ul style="list-style-type: none"> 		<ul style="list-style-type: none"> 	
Dimensions (WxHxD) mm	80x160x200	80x215x196	80x215x196	80x230x196	80x230x196	80x230x196
	(in)	(3.1x6.3x7.9)	(3.1x8.5x7.7)	(3.1x9.0x7.7)	(3.1x9.0x7.7)	(3.1x9.0x7.7)
Weight	Kg	1.3	2.3	2.5	2.9	2.9
	(lb)	(2.9)	(5.1)	(5.5)	(6.4)	(6.4)
Power Supply	80 ÷ 260 V	80 ÷ 260 V	80 ÷ 260 V	80 ÷ 260 V	80 ÷ 260 V	80 ÷ 260 V
Power	30 W	120 W	120 W	190 W	190 W	190 W



www.velp.com